

Network Working Group  
Request for Comments: 1975  
Category: Informational

D. Schremp  
J. Black  
J. Weiss  
Magnalink  
August 1996

## PPP Magnalink Variable Resource Compression

### Status of This Memo

This memo provides information for the Internet community. This memo does not specify an Internet standard of any kind. Distribution of this memo is unlimited.

### Abstract

The Point-to-Point Protocol (PPP) [1] provides a standard method of encapsulating multiple protocol datagrams over point-to-point links. The PPP Compression Control Protocol [2] provides a method for negotiating data compression over PPP links.

The Magnalink Variable Resource Compression Algorithm (MVRCA) allows a wide range of interoperable compression implementations whose performance characteristics are a function of available CPU and memory resources.

### Introduction

The Magnalink variable resource compression algorithm defines a family of interoperable compression solutions with compression performance as a function of available CPU and memory resources. It addresses the need for an algorithm which can be tailored to the system on which it is implemented without compromising interoperability.

### Licensing

Source licenses are available on a non-discriminatory basis.

The contact person for evaluation under NDA and Licensing is:

Director of OEM Sales  
Magnalink Communications Division  
Telco Systems Inc.  
63 Nahatan Street  
Norwood, Mass. 02062  
Phone: (617) 255-9400, Fax: (617) 255-5885  
oem@magna.telco.com



## Compressed/Uncompressed Flag (C)

When attempting to compress certain types of Packets or Fragments the compressor may not be effective. When this occurs the uncompressed data is added to the compression History Buffer and sent across the link in frame with the Compressed/Uncompressed Flag(C) set to 0.

## Context Identifier (CID)

Since PPP will transport multiple protocol datagrams it may be advantageous to compress each protocol or each virtual circuit in a different History Buffer or Context. The CID allows the compressor to indicate to the decompressor which History Buffer the compressor decided to use for a given Packet. The basis of this decision is up to the implementor. The number of buffers and size of each buffer is negotiated.

A CID of 0 indicates that the Packet by Packet context will be used if it has been negotiated. The Packet by Packet context is cleared between Packets so that this History Buffer is not maintained across Packet boundaries.

## Packet Integrity Byte (PIB)

To ensure that Packets are being compressed and decompressed correctly and to ensure History Buffer synchronization is maintained, a Packet Integrity Byte is added to the packet header.

The packet integrity byte is defined in the full protocol specification.

## Configuration Option Format

## Description

The CCP MVRCA Configuration Option negotiates the use of MVRCA on the link. By default or ultimate disagreement, no compression is used.

0										1										2										3											
0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9		
Type										Length										FE	P	History										# Contexts									

Type

24

Length

4

FE - Features

Negotiates features specific to this compression algorithm.

History

Defines the size of the compression history buffer. Valid values are defined in the full protocol specification.

# Contexts

This is the number of contexts. Each context implies the creation of a History Buffer for that context of the size indicated in the Context History field. Values are 1-63. This value includes both the Packet by Packet context and the number of contexts for which history is maintained. Therefore, when this value is 1 and the P (Packet by Packet) flag is also 1, then only in packet compression is supported and history context is not retained across packet boundaries. The Context Identifier (CID) starts with 1 for contexts where the history is maintained.

P - Packet by Packet flag

When 1, packet by packet compression is enabled for the context whose context ID is 0. When P is 0, packet by packet compression is not supported.

## Security Considerations

Security issues are not discussed in this memo.

## References

- [1] Simpson, W., Editor, "The Point-to-Point Protocol (PPP)", STD 51, RFC 1661, July 1994.
- [2] Rand, D., "The PPP Compression Control Protocol (CCP)", RFC 1962, June 1996.
- [3] Rand, D., "PPP Reliable Transmission", RFC 1663, July 1994.

## Acknowledgments

## Chair's Address

The working group can be contacted via the current chair:

Karl Fox  
Ascend Communications  
3518 Riverside Drive, Suite 101  
Columbus, Ohio 43221

EMail: karl@ascend.com

## Authors' Addresses

Comments about this document may also be directed to the authors.

Doug Schremp  
Telco Systems, Inc.  
Magnalink Communications Division  
63 Nahatan Street  
Norwood Ma. 02062

Phone: (617) 255-9400  
EMail: dhs@magna.telco.com

Jeffrey Black  
Telco Systems, Inc.  
Magnalink Communications Division  
63 Nahatan Street  
Norwood Ma. 02062

Phone: (617) 255-9400  
EMail: jtb@magna.telco.com

Jeffrey Weiss  
Telco Systems, Inc.  
Magnalink Communications Division  
63 Nahatan Street  
Norwood Ma. 02062

Phone: (617) 255-9400  
EMail: jaw@magna.telco.com

